自动过滤阀

Automatic Filter Valve



53502 (F71B1)



53540B (F112B)

结构性能特点 Structure Features

- LED显示，停电数据保护（3天）
- 冲洗时无原水旁通
- 可设定重复冲洗次数F-00
- 带信号输出端口(b-01/b-02)、远程控制端口、互锁端口
- 可选运行按天计或按小时计
- 可选时间型或流量型
- 可定制RS-485通信功能
- 适配电源AC100-240V/50-60Hz
- 主要型号有F67系列、F71系列、F134A、F75、F77B、F95B、F111B、F147B、F112B和F96B


- LED disp, laydate saved after power off (3 days)
- No hard water bypass in rising cycle
- Can set rinsing frequency F-00
- With signal output connector (b-01 or b-02), remote handling connector and interlock connector
- Start rising by days or hours
- Time type or meter type is for optional
- With RS-485 port is optional
- Electrical Facility：AC100-240V/50-60Hz
- Main Models：F67, F71, F134A, F75, F77B, F95B, F111B, F147B, F112B and F96B

适用场合 Applications

家用过滤设备、反渗透预处理设备的活性炭和砂过滤器、泳池过滤设备、除铁锰设备等

Residential filter equipment, sand filter or A/C filter for RO pretreatment, swimming pool filter equipment and iron/manganese removal equipment

型 号 Model				
	53502(F71B)	53502B(F71G)	53504S(F67B)	53504(F67C)
工作流程 Working Process	运行→反洗→正洗→运行 Service→Backwash→Fast Rinse→Service			
进/出水口 Inlet/Outlet	3/4"M	3/4"M	1"F	1"F
排水口 Drain	3/4"M	3/4"M	1"F	1"F
基座 Base	2.5"-8NPSM	2.5"-8NPSM	2.5"-8NPSM	2.5"-8NPSM
中心管 Riser Pipe	1.05"OD	1.05"OD	1.05"OD	1.05"OD
适配罐体 Resin Tank	6"~10"	6"~10"	6"~16"	6"~16"
流量 Flow Rate	2 m^3/h	2 m^3/h	4 m^3/h	4 m^3/h

型 号 Model	 可选485通信端口 RS-485 port is optional	 可选485通信端口 RS-485 port is optional	 可选485通信端口 RS-485 port is optional
	53518(F77B)	**53520(F95B)**	**53520T(F111B)**
工作流程 Working Process	运行→反洗→正洗→运行 Service→ Backwash→ Fast Rinse→Service		
进/出水口 Inlet/Outlet	2"M	2"M	2"M
排水口 Drain	2"M	2"M	2"M
基座 Base	4"-8UN	侧装 (2"M上下布) Side-mounted (2"M top and bottom strainer connector)	4"-8UN
中心管 Riser Pipe	1.5"D-GB		2"D-GB
适配罐体 Resin Tank	30"~36"	30"~36"	30"~36"
流量 Flow Rate	18 m^3/h	20 m^3/h	20 m^3/h

型 号 Model	 带RS-485通信端口 with RS-485 port	 带RS-485通信端口 with RS-485 port	 带RS-485通信端口 with RS-485 port
	53530(F147B)	**53540B(F112B)**	**53550(F96B)**
工作流程 Working Process	运行→反洗→正洗→运行 Service→ Backwash→ Fast Rinse→Service		
进/出水口 Inlet/Outlet	DN65	DN65	DN80
排水口 Drain	DN65	DN65	DN80
基座 Base	侧装(DN65上下布) Side-mounted (DN65 top and bottom strainer connector)	侧装(DN80上下布) Side-mounted (DN80 top and bottom strainer connector)	侧装(DN100上下布) Side-mounted (DN100 top and bottom strainer connector)
中心管 Riser Pipe			
适配罐体 Resin Tank	36"~48"	36"~48"	36"~60"
流量 Flow Rate	30 m^3/h	40 m^3/h	50 m^3/h