数码管显示控制阀（P系列）

P Series Control Valve



54502 (F71P)



74504 (F68P)

结构性能特点 Structure Features

- 采用光耦定位
- 数码管+12颗指示灯显示
- 无泄压和远程控制端口
- 可定制RS-485通信功能

- Be located by optocoupler
- Digital tube and 12 indicator lights display
- No pressure relief and remote handling connector
- With RS-485 port optional

适用场合 Applications

家用软水系统或过滤系统
锅炉给水软化系统、离子交换设备

Residential Softener or Filter system.
Boiler Softener, Ion-Exchange Equipment.

型 号 Model				
	54502(F71P)	54502-B(F71P-B)	54504(F67P)	54504-B(F67P-B)
工作流程 Working Process	运行 → 反洗 →正洗→运行 Service → Backwash → Fast Rinse → Service			
进/出水口 Inlet/Outlet	3/4"M	3/4"M	1"F	1"F
排水口 Drain	3/4"M	3/4"M	1"F	1"F
基座 Base	2.5"-8NPSM	2.5"-8NPSM	2.5"-8NPSM	2.5"-8NPSM
中心管 Riser Pipe	1.05"OD	1.05"OD	1.05"OD	1.05"OD
适配罐体 Resin Tank	6"~10"	6"~10"	6"~16"	6"~16"
流量 Flow Rate	2 m^3/h	2 m^3/h	4 m^3/h	4 m^3/h
备注 Remark		带RS-485端口 with RS-485 port		带RS-485端口 with RS-485 port

型 号 Model				
	64602(F65P)	64604(F63P)	74602(F69P)	74604(F68P)
工作流程 Working Process	运行→反洗→吸盐慢洗→盐箱补水→正洗→运行 Service → Backwash → Brine & Slow Rinse → Brine Refill → Fast Rinse → Service			
进/出水口 Inlet/Outlet	3/4"F	1"M	3/4"F	1"M
排水口 Drain	1/2"M	1/2"M	1/2"M	1/2"M
基座 Base	2.5"-8NPSM	2.5"-8NPSM	2.5"-8NPSM	2.5"-8NPSM
中心管 Riser Pipe	1.05"OD	1.05"OD	1.05"OD	1.05"OD
吸盐口 Brine Tank Connector	3/8"M	3/8"M	3/8"M	3/8"M
适配罐体 Resin Tank	6"~12"	6"~18"	6"~12"	6"~18"
流量 Flow Rate	2 m^3/h	4 m^3/h	2 m^3/h	4 m^3/h
再生方式 Regeneration Mode	顺流再生 DF	顺流再生 DF	逆流再生 UF	逆流再生 UF

数码管显示控制阀（Q系列）

Q Series Control Valve



55502 (F71Q)



65503 (F117Q)

结构性能特点 Structure Features

- 采用光耦定位
- 主控板与显示板高度集成
- 数码管+2颗指示灯显示
- 防尘罩、控制盒卡扣连接

- Be located by optocoupler
- Highly integrated main board and display board on one board
- Digital tube and 2 indicator lights display
- Dust cover and control box adopting clip connection

适用场合 Applications

家用软水系统或过滤系统
锅炉给水软化系统、离子交换设备

Residential Softener or Filter system.
Boiler Softener, Ion-Exchange Equipment.