R.O. WATER PURIFIERS · ECOPLUS SERIES · METAL FRAME

Ecoplus Pro Water Purifier

5-stage reverse osmosis · 75 GPD · 10" filter housings · With / without pump

5-stage open-frame reverse osmosis water purifier with pre-filters in standard 10" filter housings. The pre-filter cartridges are economical and easy to replace, and contamination in the housings can be seen at a glance.

Mounted on a metal frame, the unit works with an external 12 litre metal tank; a 10 bar gauge shows the feed pressure. Available with or without a pump to suit the mains pressure; an alkaline water option can be added on request.



CAPACITY	FILTRATION
75 GPD (284 L/day)	**5** stages
TANK	PUMP
12 L metal (3.2 gal)	**With / Without**

01 FILTRATION STAGES

Stage	Filter	Function	Replace
Stage 1	10" Sediment 5 µm	Retains sand, rust and sediment	6 – 12 months
Stage 2	10" GAC Carbon	Reduces chlorine, taste and odour	6 – 12 months
Stage 3	10" CTO Carbon	Reduces residual chlorine and organics	6 – 12 months
Stage 4	75 GPD Membrane Filter	Separates dissolved salts and contaminants	12 – 24 months
Stage 5	2" Inline Post Carbon (Quick-connect)	Polishes taste and odour as the final stage	6 – 24 months

Optional: an extra alkaline, mineral or bioceramic filter stage. Replacement intervals are typical values and depend on water quality and usage.

02 OPERATING CONDITIONS

Feed pressure (no pump)	3 – 7 bar
Feed pressure (with pump)	0.2 – 7 bar
Feed water temperature	5 – 38 °C (41 – 100 °F)
Feed water TDS	Max. 500 ppm
Feed water pH	3 – 11
Hardness	Max. 20 °F
Pump supply	24 V DC (via adapter)

03 TECHNICAL SPECIFICATIONS

Stock code	3-04-EPRO
Frame	Metal
Filter housing	10" spring-type housing
Tank	12 L metal tank (3.2 gal), external
Valve	Shut-off valve
Pressure gauge	10 bar
Unit size	190 × 365 × 450 mm
Warranty / service life	2 years / at least 10 years

ADDRESS
Beylikdüzü OSB, Bakır ve Pirinççiler Industrial Estate
Karanfil St. No: 3, 34520 Beylikdüzü, Istanbul, Türkiye

CONTACT
T +90 (212) 914 14 34
info@hscwater.com.tr

WEB
hscwater.com

Made in Türkiye

04 FEATURES

- 5-stage reverse osmosis filtration
- Standard 10" spring-type filter housings
- Metal open frame
- Pressure monitoring with 10 bar gauge
- Available with or without pump

05 APPLICATIONS

- Drinking and cooking water at home
- Under-sink kitchen installations
- Offices and small businesses
- Treatment of mains water

06 INSTALLATION AND MAINTENANCE

01 Shut the cold water valve; fit the connection kit (feed adapter) to the cold water line.

02 Drill the worktop first with a 5 mm, then a 12 mm bit and mount the faucet.

03 Place the membrane in its housing; cut the 1/4" tubing into three and connect the inlet, faucet and drain lines.

04 Open the valve (plug in the adapter on pump models); wait 1 hour for the tank to fill.

05 Drain the first tank through the faucet; once it refills, the unit is ready for use.

Do not connect the unit to hot water (above 40 °C). Pressure: below 3 bar use the pump model or a pump kit; above 7 bar fit a pressure reducer at the inlet. Replace the filters at least once a year; if unused for over a month, close the valve and empty the tank.

07 LOGISTICS

Model	Box Size (mm)	Box Weight
No pump	275 × 430 × 485	8.45 kg
With pump	275 × 430 × 485	13.35 kg
3.2 G tank	280 × 280 × 365	3.72 kg

Vehicle	Pallets	Boxes / Pallet	Palletised	Loose
20' Container	10	32	320 pcs	420 pcs
40' DC Container	20	32	640 pcs	864 pcs
40' HC Container	20	40	800 pcs	1,080 pcs
Curtain-side Truck	26	40	1,040 pcs	1,240 pcs

Quantities are for units only; tanks are not included. Pallet size: 100 × 120 cm (ISO pallet).







pH ~8.5+ ALKALİ SU
Seçeneği ile Tercih Edebilirsiniz.

Optional Alkaline Water Stage

A 2" inline alkaline filter fitted as an optional extra stage adds minerals such as calcium and magnesium to the reverse osmosis water and raises its pH to about 8.5 or above, giving a softer taste. Specify when ordering.

The technical values in this document are for information purposes only and were obtained under standard test conditions. Actual performance may vary depending on water quality, temperature, pressure and operating conditions. HSC Water reserves the right to change technical specifications without prior notice as part of ongoing product development.

ADDRESS
Beylikdüzü OSB, Bakır ve Pirinççiler Industrial Estate
Karanfil St. No: 3, 34520 Beylikdüzü, Istanbul, Türkiye

CONTACT
T +90 (212) 914 14 34
info@hscwater.com.tr

WEB
hscwater.com

Made in Türkiye