RO SPARE PARTS AND ACCESSORIES · RO FAUCETS

RON Cartridge Swan-Neck Quick Faucet (PLS)

For reverse osmosis units · Replaceable faucet cartridge · Quick-connect stem 4/6, food-grade plastic

Countertop swan-neck faucet for reverse osmosis units and water purifiers. Thanks to its cartridge design, only the faucet cartridge (3-RY-MUS-YED-RON-K) is replaced in case of wear or failure, not the whole faucet.

It has a 4/6 plastic quick-connect stem made of food-grade, high-strength material; 4/6 unit tubing is fitted without tools.



MODEL **Swan-Neck**	CONNECTION **Quick** 4/6 stem, plastic
CARTRIDGE **Replaceable**	ORIGIN **Türkiye**

01 MODELS AND DIMENSIONS

Stock Code	Model	Connection
3-RY-MUS-RON-K-PLS	RON Cartridge Swan-Neck Quick Faucet	Quick stem 4/6 (plastic)
3-RY-MUS-YED-RON-K	Faucet Cartridge (spare)	—

The faucet is supplied with its cartridge fitted. The 3-RY-MUS-YED-RON-K spare cartridge is sold individually.

02 OPERATING CONDITIONS

Use	**RO and purifier outlet**
Connection	**Quick-connect stem 4/6, food-grade plastic**
Mounting	**Countertop, hole-mounted**
Cartridge change	**In seconds, without removing the faucet**

03 MATERIALS

Body	**Metal, bright chrome finish**
Faucet cartridge	**Replaceable (3-RY-MUS-YED-RON-K)**
Lower connection	**Quick stem 4/6, food-grade plastic**
Origin	**Türkiye**

ADDRESS
Beylikdüzü OSB, Bakır ve Pirinççiler Industrial Estate
Karanfil St. No: 3, 34520 Beylikdüzü, Istanbul, Türkiye

CONTACT
T +90 (212) 914 14 34
info@hscwater.com.tr

WEB
hscwater.com

Made in Türkiye

04 FEATURES

- No more faucet replacement: just renew the cartridge
- Cartridge change in seconds at minimum cost
- Tool-free tubing installation with quick connection
- Food-grade, high-strength plastic connection
- Swan-Neck design

05 APPLICATIONS

- Under-sink reverse osmosis units
- Purifier service and spare part
- Home and office kitchens

06 INSTALLATION AND CARTRIDGE CHANGE

01 Drill a mounting hole of suitable size in the countertop and fix the faucet with the lower nut.

02 Push the unit outlet tubing fully into the faucet's lower quick fitting.

03 Start the unit and check the connection for leaks.

04 To change the cartridge, shut off the unit water, remove the old cartridge and fit the new one.

> Use the faucet on treated cold water lines only. Do not use abrasive cleaners.

07 PACKAGING

Stock Code	Box Size (mm)	Pcs per Box
3-RY-MUS-RON-K-PLS	-	-

Please contact our sales team for packaging details.





Faucet cartridge 3-RY-MUS-YED-RON-K

The technical values in this document are for information purposes only and were obtained under standard test conditions. Actual performance may vary depending on water quality, temperature, pressure and operating conditions. HSC Water reserves the right to change technical specifications without prior notice as part of ongoing product development.

ADDRESS
Beylikdüzü OSB, Bakır ve Pirinççiler Industrial Estate
Karanfil St. No: 3, 34520 Beylikdüzü, Istanbul, Türkiye

CONTACT
T +90 (212) 914 14 34
info@hscwater.com.tr

WEB
hscwater.com

Made in Türkiye